US007893928B2

US 7,893,928 B2

(12) **United States Patent**
Im

(10) **Patent No.:** **US 7,893,928 B2**
(45) **Date of Patent:** **Feb. 22, 2011**

(54) **COMPUTER SYSTEM AND CONTROL METHOD THEREFOR**

(75) Inventor: **Jae-seong Im**, Yongin-si (KR)

(73) Assignee: **Samsung Electonics Co., Ltd.**, Suwon-Si (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 958 days.

(21) Appl. No.: **11/746,262**

(22) Filed: **May 9, 2007**

(65) **Prior Publication Data**

US 2008/0062138 A1 Mar. 13, 2008

(30) **Foreign Application Priority Data**

Sep. 11, 2006 (KR) 10-2006-0087576

(51) **Int. Cl.**
G06F 3/041 (2006.01)
(52) **U.S. Cl.** **345/173**; 345/168; 345/179
(58) **Field of Classification Search** 345/173–179
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,956,021 A * 9/1999 Kubota et al. 345/179

FOREIGN PATENT DOCUMENTS

CN	1383050	12/2002
CN	1777858	5/2006
JP	2005-326905	11/2005
KR	2001-19498	3/2001
KR	2003-35226	5/2003
KR	2005-48758	5/2005

* cited by examiner

Primary Examiner—Nitin Patel
(74) *Attorney, Agent, or Firm*—Jefferson IP Law, LLC

(57) **ABSTRACT**

A computer system includes a touch pad having plural key areas and generating a key signal according to a touch input with respect to the respective key areas, a display, a storing unit for storing a relation table of the character value corresponding to the key area, and a controller reading the character value corresponding to the concerned key area from the storing unit and displaying the same on the display if a key signal is generated in the touch pad, and if the key signals are successively generated with respect to the plural key areas, sequentially converting and displaying the character values corresponding to the successive key areas.

23 Claims, 5 Drawing Sheets